

B

B106 PIERCING CONNECTOR LOW VOLTAGE



PRODUCT DESCRIPTION:

PC T ab(B) x/y

PC = Piercing CONNECTOR

T = Tear head; B= BARE; a= bolt No.; b= outlet number;

x= Max of main cond.; y= Max of Tap cond.

PRODUCT RANGE:

PCT13C 95/95 RE/RM, isolated 16-95/ isolated 16-95 mm², Cu/Al.

PCT13CB 95/95 RE/RM, isolated 16-95/ bare 16-95 mm², Cu/Al.

PCT13C 150/150 RE/RM, isolated 16-150/ isolated 16-150 mm², Cu/Al.

PCT13CB 150/150 RE/RM, isolated 16-150/ bare 16-150 mm², Cu/Al.

USED MATERIALS:

UV & fire resistant PA66, PVC, dacromet or H.D.G.(optional) finished steel, tinned copper.

* Brass or Aluminum should be required

VARIANTS:

The product is manufactured and supplied in modification's as is showed upwards in PRODUCT RANGE.

PACKING:

120pcs per carton. G.W:25 kg N.W: 26kg

STORAGE AND TRANSPORT:

Product do not have any specific requirements on storage. It is fire-resistant and it is not dangerous.

