

D201 Straight Line Strain Clamp

Product description:

Dead ends bolted Aluminum Straight line strain clamp for distribution and light transmission construction with all aluminum, ACSR or aluminum alloy conductor. These clamps have high holding power and large range taking ability. (Straight Contoured Groove).

Product range:

TYPE	Dimension						Conductor Range	U Bolts		Pin Bolt	ULTIMATE BODY STRENGTH (KG)	
	A	B	L	W	D1	D2		No.	Size			
ASC-1	1" (25.4mm)	2 1/8" (53.98mm)	5 3/8" (136.52mm)	11/16" (17.46mm)	1 5/8" (41.27mm)	1 1/8" (28.57mm)	3/4" (19.05mm)	0.18"-0.47" (4.57-11.94mm)	2	M12	M16	3175kg
ASC-2	1" (25.4mm)	3 1/2" (88.9mm)	6 3/4" (171.45mm)	11/16" (17.46mm)	1 5/8" (41.27mm)	1 1/8" (28.57mm)	3/4" (19.05mm)	0.47"-0.64" (11.94-16.26mm)	2	M12	M16	3629kg
ASC-3	1" (25.4mm)	3 7/8" (98.43mm)	7 5/8" (190.5mm)	11/16" (17.46mm)	1 5/8" (41.27mm)	1 1/8" (28.57mm)	3/4" (19.05mm)	0.64"-0.88" (16.26-22.35mm)	2	M12	M16	4536kg

Used materials:

Body and keeper : aluminum alloy.
 Hardware: galvanized steel.
 Socket and Clevises: Iron, galvanized
 Cotter Pin : Stainless steel

Variants:

The product is manufactured and supplied in modification's as is showed upwards in product range.

Storage and transport:

Product do not have any specific requirements on storage. It is fire-resistant and it is not dangerous.

